

=====

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

=====

PRODUCT NUMBER: 452
IDENTITY: 200M

Revision Date: 01/23/2003

Section I

Manufacturer's Name: QWEST CHEMICAL CORPORATION
Address: 12255 FM 529
NORTHWOODS INDUSTRIAL PARK
HOUSTON
State: TX Zip Code: 77041

Telephone Numbers:
Emergency:
800/255-3924
Information:
713/8968188

HMS CODES: REACTIVITY: 1 FLAMMABILITY: 3 HEALTH: 2 PERSONAL PROTECT: B

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory)

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	†
AROMATIC PET. DISTILLATES	64742-94-5	NOT EST.	NOT EST.		---
ISOPROPYL ALCOHOL	67-53-0	400 PPM	400 PPM	N/A	---
PROPANE/N-BUTANE	68476-86-8	1000 PPM	600 PPM	N/A	---
-----	-----	-----	-----	-----	-----
-----	-----	-----	-----	-----	-----
-----	-----	-----	-----	-----	-----
-----	-----	-----	-----	-----	-----
-----	-----	-----	-----	-----	-----

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point:	350F+	Specific Gravity (water=1)	0.69
Vapor Pressure(mm Hg)	<5	Melting Point:	N/A
Vapor Density(AIR=1)	4	Evaporation Rate:	<1
Solubility in water:	0%	(Butyl Acetate=1)	

Appearance and Odor: BROWN COLORED SPRAY, PETROLEUM ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point(Method Used): 142F TCC Flammable Limits: LEL: 1.0 UEL: 3.0
Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO
TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. MAY DEVELOP A FLAMMABLE
ATMOSPHERE IN CONFINED AREAS